



	7121-01 Legendary 7121-02 Intuitive	7121-08 Flow 7121-09 Ovation
13 Colorways:	7121-03 Hopeful	7121-10 Luxurious*
	7121-04 Growth	7121-11 Radiance
	7121-05 Intrigue	7121-12 Spirit
	7121-06 Reflection	7121-13 Embrace*
	7121-07 Romance	

<sup>\*</sup>These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	The Alpha Workshops		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	18 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Non-Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test<sup>1</sup>

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test<sup>2</sup>

- Meets requirements for Flame Spread, Smoke Developed, and Flashover  $\,$ 

 $1\ When applied to\ GRC\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\$ 

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

## 3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com