



16.6.1	9B21-02 Crystal Lattice	9B21-52 Knighthood*
	9B21-22 Golden Pearl	9B21-55 Shields Up!*
	9B21-35 Aladdin's Lamp	9B21-58 Oxidized*
	9B21-38 Anodize	9B21-59 Gyrados*
16 Colorways:	9B21-41 Pendant	9B21-65 Merlin
	9B21-44 Copperclad*	9B21-79 Grail*
	9B21-47 Brass Ring	9B21-80 Hammered Steel
	9B21-49 Hot Tin Roof*	9B21-90 Excalibur

\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

		- · · - · · · · · · · · · · · · · · · ·		
Designer	Sondra Alexander			
Total Weight	21.0 oz. ply (651 g. plm.) 14.0 oz. psy (475 g. psm.)	Vertical Repeat	N/A	
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A	
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.	
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Reverse Hang, Random Match	
Tear (Minimum)	25 × 25 lb <sub>f</sub> (111 × 111 N)	WA Spec.	WA-101, Type II	
Federal Spec.	CCC-W-408A, Type II	ASTM F-793	Category V, Type II	
	NFPA 101® Life Safety Code®			
	NFPA 255 (ASTM E-84, CAN UL S102M) Tunnel Test <sup>1</sup>			

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test<sup>2</sup>

- Meets requirements for Flame Spread, Smoke Developed, and Flashover

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com