



24 Colorways:	SE21-01 Loom	SE21-13 Oatmeal	
	SE21-02 Cotton	SE21-14 Cambric	
	SE21-03 Tabby	SE21-15 Flax	
	SE21-04 Manila	SE21-16 Madder	
	SE21-05 Fleece	SE21-17 Angora	
	SE21-06 Nettle	SE21-18 Lawn	
	SE21-07 Flaxen	SE21-19 Jute	
	SE21-08 Holland	SE21-20 Hemp	
	SE21-09 Linum	SE21-21 Woolsey	
	SE21-10 Safflower	SE21-22 Mohair	
	SE21-11 Sky	SE21-23 Abaca	
	SE21-12 Agave	SE21-24 Cashmere	
	Designer	Koroseal	
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.