



E222-10 Earnest

9 Colorways:

E222-35 Naples E222-37 Expectation

E222-55 Baroness E222-70 Red Hilda E222-71 Marie*

E222-75 Portrait of a Lady*

E222-91 Poplar E222-98 Smoke

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	3 in.
Roll Width	53-55 in. (134-140 cm.)	Horizontal Repeat	3.375 in.
Backing	Non-Woven	Nominal Pattern Width	51-52 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 × 25 lb _f (111 × 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
	NFPA 101® Life Safety Code®		

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, and Flashover

 $1\ When applied to\ GRC\ board\ with\ A-848-B\ adhesive\\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ board\ with\ A-848-B\ adhesi$

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com