

| | US UNITS | METRIC UNITS |
|---|---|--|
| Nominal Weight | 16.0 oz PLY 10.7 oz PSY | 500 g PLM 360 g PSM |
| Weight Savings | Absence of chlorine provides a lower molecular weight polymer, therefore, making the wallcovering lighter for the same thickness. -Reduced freight costs -Easier handling of rolls for safety | |
| Roll Width | 54/55 in. | 134/140 cm |
| Fabric | Non-Woven | |
| Washability/Scrubability | Meets 300 Cycle Requirements | |
| Stain Resistance | Premium stain and abrasion resistant water-based coating applied | |
| Post Consumer Recycled Content | Contains a minimum of 20% | |
| Fire Testing | NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover | |
| Combustion Toxicity | Pittsburgh Protocol - Meets the New York City Requirements | |
| Indoor Air Quality | California 01350 - Tested to and meets emission requirements for schools and offices. | |
| Repeat | Vertical Horizontal Nominal Pattern Width Match Information | N/A N/A 51 in. 130 cm Random Match, Reverse Hang |
| Does not contain chlorine or other halogen compound. Contains no plasticizers including phthalates. Printing inks are water-based. | | |
| 1 When applied to GRC Board with A-848-B adhesive | | 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive |

Available in 5 Colorways

- *P419-10
- *P419-32
- *P419-36
- *P419-53
- *P419-88

***These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**