

Shapes cut from a canvas can become anything from lace to architectural embellishments. Layering with these designs can add a delicate touch or a bold statement when placed over a surface. Imagine what lies within.

	US UNITS	METRIC UNITS
Total Weight	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	52" – 54"	132 - 137cm
Gauge	.021"	0.53 mm
Fabric	Non-woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 13501 – 1:2007 + EN15102:2007 + A1:2011 California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A" N/A" 51" Random Match, Non-Reverse Hang
1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

Available in 18 Colorways

67180	67181	67193
67182	67183	67194
67185	67186	67195
67187	67188	*67196
*67189	*67190	67197
67191	67192	67198

*** These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**