

CLEANING AND MAINTENANCE



CLEANING

The cleaning process is an important part of the installation process of Arbor's overall appearance. Adhesive and paste residue left on the surface of the wood species can become a problem later if not cleaned off during the installation process.

It is recommended to clean the surface of the Arbor Wood Wallcovering with clean water once or twice during the final installation process. A lint-free cloth or a good grade sponge can be used for this process.

If adhesive or paste is not cleaned off, the surface will become cloudy or look milky white after a 30 to 60 day period following the installation. If this occurs it is recommended to use an adhesive cleaning chemical by Zinsser Co. called DIFF. DIFF can be purchased locally at a paint supply stores.

MAINTENANCE

Arbor with Standard Finish

Maintenance on Standard Finish Arbor Wood Wallcovering is recommended to be done once a year and not more than twice a year as follows:

- A. Clean the entire surface of all exposed wood by using Murphy's Oil Soap, following directions by the manufacturer. The wood surface may also be cleaned with warm clean water using a damp lint-free cloth or sponge.

Arbor with Ultra Finish

Maintenance on Ultra Finished Arbor Wood Wallcovering is recommended as follows:

- A. Follow instructions as directed in Standard Finished Arbor.
- B. Ultra Finished Arbor can be cleaned with Fantastic or 409 household cleaners and a lint-free cloth; then a clean water rinse (this can be done as needed to clean surface of the Arbor).
- C. Disinfecting wipes (utilized in healthcare environments or restaurants) may be used to clean the surface, followed by a clean water rinse.
- D. Melamine foam sponges (ie. magic erasers) can be used to remove scuffs from the surface.

DO NOT USE ANY ABRASIVE CLEANERS OR PADS ON THE SURFACE OF ARBOR WOOD WALLCOVERINGS.