



| | | | |
|---------------|-----------------|-------------------|------------------|
| 24 Colorways: | SE81-01 Loom | SE81-09 Linum | SE81-17 Angora |
| | SE81-02 Cotton | SE81-10 Safflower | SE81-18 Lawn |
| | SE81-03 Tabby | SE81-11 Sky | SE81-19 Jute |
| | SE81-04 Manila | SE81-12 Agave | SE81-20 Hemp |
| | SE81-05 Fleece | SE81-13 Oatmeal | SE81-21 Woolsey |
| | SE81-06 Nettle | SE81-14 Cambric | SE81-22 Mohair |
| | SE81-07 Flaxen | SE81-15 Flax | SE81-23 Abaca |
| | SE81-08 Holland | SE81-16 Madder | SE81-24 Cashmere |

| | | | |
|-------------------|--|-----------------------|----------------------------|
| Designer | Koroseal | Vertical Repeat | N/A |
| Total Weight | 20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.) | Horizontal Repeat | N/A |
| Roll Width | 52-54 in. (132-137 cm.) | Nominal Pattern Width | 51 in. |
| Backing | Non-Woven | Match Information | Reverse Hang, Random Match |
| Content | Thermo Polymer Olefin | WA Spec. | WA-101, Type II |
| Tensile (Minimum) | 50 x 55 lb _f (222 x 245 N) | ASTM F-793 | Category V, Type II |
| Tear (Minimum) | 25 x 25 lb _f (111 x 111 N) | Federal Spec | CCC-W-408D, Type II |

NFPA 101® Life Safety Code®

Fire Testing

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹
- Class A Rating

NFPA 286 Corner Burn Test²
- Meets requirements for Flame Spread, Smoke Developed, & Flashover

¹ When applied to GRC board with A-848-B adhesive ² When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.