



20 Colorways:	T183-01 Parchment	T183-09 Sagebrush	T183-44 Teak
	T183-02 Simply White	T183-10 Indigo	T183-46 Beam
	T183-03 Sky	T183-11 Ebony	T183-48 Walnut
	T183-04 Driftwood	T183-13 Glazed	T183-50 Rosewood
	T183-05 Saddle	T183-14 Maple	T183-95 Smoked
	T183-06 Sandstone	T183-16 White Oak	T183-99 Charred
	T183-07 Graphite	T183-42 Ash	

Designer	Koroseal	Vertical Repeat	N/A
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Horizontal Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Nominal Pattern Width	51 in.
Backing	Non-Woven	Match Information	Non-Reverse Hang, Random Match
Content	Thermo Polymer Olefin	WA Spec.	WA-101, Type II
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	ASTM F-793	Category V, Type II
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	Federal Spec	CCC-W-408D, Type II

Fire Testing	NFPA 101® Life Safety Code®
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover

1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.