

COLOR-MATCHED CAULK

Product Description: Korogard Wall Protection Systems provides an acrylic-based, evaporative cure sealant with a special silicone modifier that is color-matched to Korogard Protective Wallcovering standard colors. Korogard caulk is packaged in 10.5 oz. cartridges.

Product Uses: Korogard caulk will help provide a Korogard Protective Wallcovering installation with a finished appearance. Korogard caulk may be used as an alternative to moldings for inside corners and for the expansion gap between sheets. Korogard caulk will still allow for the normal thermal expansion of Korogard Protective Wallcovering when extruded into the required 1/16 in. (1.59 mm.) gap. When applied properly, Korogard caulk will provide waterproof seam treatment.

Installation: Surfaces should be free of oils, dust, old caulking, or other contaminants. Korogard caulk may be installed between temperatures of 65°F (18°C) and 80°F (27°C). The caulk darkens to color-match as it dries. A 10.5 oz. tube of caulk provides approximately 95 linear feet of coverage. Joint dimensions should not exceed 3/8 in. (9.53 mm.) x 3/8 in. (9.53 mm.). Tooling is recommended immediately after application to ensure firm contact with joint interfaces. Hands and tools should be cleaned with soapy water before the caulk dries.

Specification: Color-matched caulk shall be provided by Koroseal[®]. The caulk shall be acrylic-based with a silicone modifier. The caulk shall have the same color number as the Korogard Protective Wallcovering. Specification typically falls under Section 2.8 Part D.

The suggestions and data in this document are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale.