

3875 Embassy Parkway Fairlawn, OH 44333

(800) 828-4556 www.koroseal.com

## **Promenade** FACT SHEET

Like the leisurely march of guest into a ballroom, Promenade will dance with the walls it saunters on to. Its clean graceful lines exhibit itself as a soft geometric pattern that can make a bold statement in sophisticated, rich colors or relax the atmosphere in a lighter neutral palette of pearl essence. It's quaint, smaller companion, Courtyard, offers the same design on a smaller scale that can lend itself to a geometric texture.

	US UNITS	METRIC UNITS		
Total Weight	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM		
Roll Width	53/55 in.	134/140 cm		
Gauge (avg)	0.020 in.	0.51 mm		
Fabric	Nonwoven	Nonwoven		
Tensile (Minimum)	50 x 55 lb <sub>f</sub>	222 x 245 N		
Tear (Minimum)	25 x 25 lb <sub>f</sub>	111 x 111 N		
Federal Spec	CCC-W-408D, Type II	CCC-W-408D, Type II		
WA Spec	WA-101, Type II	WA-101, Type II		
ASTM F-793	Category V, Type II	Category V, Type II		
Fire Testing	NFPA 255 (UL723, CAN S10 Class A Rating Flame S Smoke I NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements	Flame Spread 10 Smoke Developed 5		
Indoor Air Quality		California 01350 - Meets emission requirements for schools and offices		
~ .				
Repeat Vertical   Horizontal Nominal Pattern Width   Match Information Notes and the second secon	18 in. 52 in. 52 in. Straight Match, Non-Reverse I	45.72 cm 132 cm 132 cm Hang		
1 When applied to GRC Board with A-848-B adhesiv	2 When applied to 5/8" Type-	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive		

## **Available in 9 Colorways**

P522-61	Barista	P522-16	Interlude
P522-98	Boudoir	P522-50	Serendipity
P522-23	Crush	P522-11	Timid
P522-92	Curiosity*	P522-70	Venetian*
P522-18	Flirt		

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Vinyl wallcovering has a multitude of characteristics that allow it to provide an attractive and serviceable wall surface. One of the characteristics of vinyl wallcoverings is very low moisture permeability. Therefore, it is important to assure that there are no deficiencies in the design, construction and maintenance of a building that allows moisture to accumulate in a wall cavity. The use of a vinyl wallcovering is used a deficient circumstance would result in the vinyl wallcovering acting as a vapor barrier and restricting the passage of the moisture and increasing the chance of mold growth. It is recommended that walls be checked with a suitable moisture meter prior to installation and the moisture content should not exceed 4%. Wallcovering should not be installed on a wall until water/moisture incursion has been eliminated. On renovation projects, examine walls that are to receive wallcovering and assure they do not exhibit any mold/mildew. All mold and mildew must be removed and surfaces treated to inhibit future growth. In order to reduce the risk of mold/mildew, Koroseal Interior Products, LLC utilized an inhibitor in the wallcovering. The company can also provide a service of microventing the wallcovering whereby more than 25,000 micro-holes /hZ are fused through the vinyl thereby making it permeable.

Koroseal<sup>®</sup> is a registered trademark of Koroseal Interior Products, LLC NFPA 101<sup>®</sup> and Life Safety Code<sup>®</sup> are registered trademarks of National Fire Prevention Association 63-47-P522/03/2015