



8 Colorways:	YN21-01 Fluff	YN21-05 Beeswax
	YN21-02 Chalk	YN21-06 Frogging
	YN21-03 Thread	YN21-07 Felt
	YN21-04 Notions	YN21-08 Goldwork*

^{*}This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	24 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Non-Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel $Test^1$

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test²

- Meets requirements for Flame Spread, Smoke Developed, & Flashover

 $1\ When applied to\ GRC\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\ When\ board\ with\ A-848-B\ adhesive \\ 3\$

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com