Arte®

3875 Embassy Parkway Fairlawn, OH 44333

koroseal.com

855.753.5474

Silkx Raw

FACT SHEET

		US UNITS	METRIC UNITS	
Total Weight		20 oz PLY 13 3 oz PSY	618 451 g PSM	
Roll Width		52''-54''	132 - 137cm	
Gauge		.025"	0.635 mm	
Fabric		Woven		
Tensile (Minimum)		$50 \text{ x} 55 \text{ lb}_{f}$	222 x 245 N	
Tear (Minimum)		$25 \ x \ 25 \ lb_{\rm f}$	111 x 111 N	
Federal Spec		CCC-W-408A, Type II		
WA Spec		WA-101 - 2011, Type II		
ASTM F-793		Category V, Type II		
Fire Testing CE Certification		NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed EU classification in accordance with EN15102:2007 + A1:2011		
CE Cenijica	uion	EU classification in acco	bidance with EN13102.2007 + A1.2011	
Indoor Air Quality		California 01350 - Meets emission requirements for schools and offices		
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Random Match, Non-R	everse Hang	
1 When appl	lied to GRC Board with A-848-B adhesive	2 When applied to 5/8" type-	-X gypsum board with A-848-B adhesive	

Available in 12 Colorways

67490	*67495	*67500
67491	*67496	67501
67492	67497	
67493	67498	
67494	67499	

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing. 3875 Embassy Parkway Fairlawn, OH 44333

855.753.5474

koroseal.com

Silkx Raw (Mylar)

FACT SHEET

		US UNITS	METRIC UNITS	
Total Weight		20 oz PLY 13 3 oz PSY	618 451 g PSM	
Roll Width		52'' – 54''	132 - 137cm	
Gauge		.025"	0.635 mm	
Fabric		Non-Woven		
Tensile (Minimum)		50 x 55 lb _f	222 x 245 N	
Tear (Minimum)		25 x 25 lb _f	111 x 111 N	
Federal Spec		CCC-W-408A, Type II		
WA Spec		WA-101 - 2011, Type II		
ASTM F-793		Category V, Type II		
Fire Testing CE Certification		NFPA 101 [®] Life Safety Code [®] NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed EU classification in accordance with EN15102:2007 + A1:2011		
Indoor Air Quality		California 01350 – Meets emission requirements for schools and offices		
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Random Match, Non-I	Reverse Hang	
1 When appl	lied to GRC Board with A-848-B adhesive	2 When applied to 5/8" typ	e-X gypsum board with A-848-B adhesive	

Available in 1 Colorway

67502