

ECO-A.R.T.™ by HYTEX®

ACOUSTIC RECYCLED TEXTILES

Wallcoverings • Panels • Partitions

A dimensional fabric produced with post-consumer recycled fiber offering exceptional performance, unmatched fade resistance, and a fire/smoke retardant Class A rating. It is lightweight and easy to install and maintain.

ECO-A.R.T.™ is moisture resistant, mildew, rot, and bacteria resistant and is nonallergenic.

- **eco-fi®** Polyester staple fiber. High strength fibers which are resistant to shrinking and stretching. Highly durable.
- 100% post-consumer recycled content from water & soda bottles.
- Easy to clean and maintain.
- Fiber does not absorb moisture
- Acoustical qualities: NRC ratings .05 (ASTM C423)
- Passes UBC 8-2/NFPA 265 Corner Burn Test. It is the standard test method for evaluating room fire growth contribution of Textile Wallcovering.
- Solution dyed. Resists sun, fading - colors are fast to most destructive agents.

APPLICATIONS

DESIGNERS	HEALTH CARE	HOSPITALITY	CORPORATE	INSTITUTIONAL	ENTERTAINMENT
Commercial Interiors Market	Retirement Facilities Nursing Homes Hospitals Nursing Stations	Ball Rooms Conference Rooms Meeting Rooms	Executive Conference Rooms General Offices	Schools(Auditorium) Government & Mass Trans. Buildings Day Care Centers	Theatres Recreational Centers

Acoustical Panels • Tack Boards • Elevators • Ceiling Tiles • Office Partitions • Chair Rails

PLISSÉ SPECIFICATIONS

CONTENT	BACKING	WEIGHT	WIDTH	ROLL SIZE	FLAMMABILITY
eco-fi® Post-Consumer Recycled Solution Dyed Polyester Staple Fiber	Radiant Fused	13 ounces / face weight	54"	50 yards	Class A/ASTM E-84 UBC 8-2 Flame spread: 20 / Smoke: 30
NRC	MOISTURE REGAIN	COLORFASTNESS TO LIGHT	ABRASION RESISTANCE		
(ASTM C-423) .05 over gypsum board	(ASTM D-2654) .3%	(AATCC-16A) Class 5 - 100 hours	(ASTM D-4158) Voluntary Prod. TS198 Full Commercial Serviceability		

