

Concord is an edgy take on the folded linen textures of the past. The vertical linen emboss is slashed with hard edged lines to give the pattern a dramatic finish.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.022"	0.56 mm
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA 101 - 2011, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® ASTM E-84 Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed & Flashover	
<b>CE Certification</b>	EU classification in accordance with EN15102:2007 + A1:2011 Fire Behavior – B Smoke Production – s <sup>2</sup> Flame Droplets – d <sup>0</sup>	
<b>Repeat</b>	Vertical	N/A
	Horizontal	N/A
	Nominal Pattern Width	51"
	Match Information	Reverse Hang
	1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

## Available in 8 Colorways

67240	67244
67241	*67246
67242	*67250
*67243	67251

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Concord is an edgy take on the folded linen textures of the past. The vertical linen emboss is slashed with hard edged lines to give the pattern a dramatic finish.

	US UNITS	METRIC UNITS
<b>Total Weight</b>	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.020"	0.56 mm
<b>Fabric</b>	Non-woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA 101 - 2011, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>CE Certification</b>	EU Classification in accordance with EN15102:2007 + A1:2011 Fire Behavior – B Smoke Production – s <sup>1</sup> Flame Droplets – d <sup>0</sup>	
<b>Repeat</b>	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

**Available in 4 Colorways**

- 67245
- 67247
- 67248
- 67249

**These Mylar Wallcoverings require special handling and have specific installation instructions. Please refer to Koroseal's Mylar Wallcovering Installation Instructions for further details.**