Arte®

3875 Embassy Parkway Fairlawn, OH 44333



koroseal.com



From the beginning of time, a simple drawn line is the start of a vision. Once distributed, curved, broken, angled or strung, the line becomes the reality of a vision. Beautiful in its simplest form, sophisticated and surprising once it's moved.

		US UNITS	METRIC UNITS	
Total Weight		20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM	
Roll Width		52" – 54"	132 - 137cm	
Gauge		.021"	0.53 mm	
Fabric		Woven		
Tensile (Minimum)		50 x 55 lb _f	222 x 245 N	
Tear (Minimum)		25 x 25 lb _f	111 x 111 N	
Federal Spec		CCC-W-408A, Type II		
WA Spec		WA-101, Type II		
ASTM F-793		Category V, Type II		
Fire Testing		NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test² Meets requirements for Flame Spread, Smoke Developed and Flashover		
CE Certification		EU classification in accordance with EN 13501 – 1:2007 + EN15102:2007 + A1:2011 California 01350 – Meets emission requirements for schools and offices		
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51" Random Match, Non-Rev	verse Hang	
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X	2 When applied to 5/8" type-X gypsum board with A-848-B adhesive	

Available in 16 Colorways

67200	67201	*67213
67202	67204	67214
67205	67206	*67215
67207	*67209	*67216
67208	67210	
67211	67212	

^{*} These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.