



	67524*					
5 Colorways:	67522* 67523*					
50.	67521					

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Arte®							
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	24 in.					
Roll Width	53-55 in. (135-140 cm.) Horizontal Repeat		52 in.					
Backing	Non-Woven	Nominal Pattern Width	51 in.					
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match					
Tear (Minimum)	25 × 25 lb _f (111 × 111 N)	WA Spec.	WA-101, Type II					
Federal Spec.	CCC-W-408D, Type II ASTM F-793		Category V, Type II					
	NFPA 101® Life Safety Code®							
Fire Testing	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating							
The resumg	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover							
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive							
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011							
Indoor Air Quality	loor Air Quality California 01350 – Meets emission requirements for schools and offices							

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com