



10 Colorways:	CR21-01 Organic CR21-02 Illusion CR21-03 Opalescence CR21-04 Mineral CR21-05 Sand Drift	CR21-06 Infused CR21-07 Lunar CR21-08 Fascination CR21-09 Mottled CR21-10 Prosper
Designer	Koroseal	
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat 24 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat 52 in.
Backing	Woven (Osnauburg)	Nominal Pattern Width 51 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information Reverse Hang, Match Rectangles
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec. WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793 Category V, Type II
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, and Flashover <small>1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small>	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
 ©2024 Koroseal Interior Products, LLC.