



9 Colorways:	3B22-01 Pebble 3B22-02 Smoke 3B22-05 Pearl	3B22-06 Ebony 3B22-07 Truffle 3B22-15 Graphite	3B22-16 Alabaster 3B22-17 Java 3B22-18 Walnut
Designer	Sondra Alexander		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	33 in.
Roll Width	54-55 in. (137-139 cm.)	Horizontal Repeat	54 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width	54 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating		
	NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, and Flashover		
	1 When applied to GRC board with A-848-B adhesive    2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

For additional technical information please visit [koroseal.com](http://koroseal.com)

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association  
 ©2024 Koroseal Interior Products, LLC.