

7 Colorways:	R119-06 R119-40* R119-49* R119-61* R119-90* R119-91* R119-96*		
<small>*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.</small>			
Designer	Koroseal		
Total Weight	16.0 oz. ply (500 g. plm.) 10.7 oz. psy (360 g. psm.)	Vertical Repeat	36 in.
Roll Width	54-55 in. (134-140 cm.)	Horizontal Repeat	8.625 in.
Backing	Non-Woven	Nominal Pattern Width	52 in.
Match Information	Non-Reverse Hang, Maintain Vertical Band Width		
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, and Flashover <small>1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small>		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		
Weight Savings	Absence of chlorine provides a lower molecular weight polymer, therefore making the wallcovering lighter for the same thickness.		
Washability/ Scrubability	Meets 300 Cycle Requirements		
Stain Resistance	Premium stain and abrasion resistant water-based coating applied		
Combustion Toxicity	Pittsburgh Protocol - Meets the New York City Requirements		
Post Consumer Recycled Content	Contains a minimum of 20%		
For additional technical information please visit koroseal.com			

 3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal[®] is a registered trademark of Koroseal Interior Products, LLC.
 NFPA 101[®] and Life Safety Code[®] are registered trademarks of National Fire Prevention Association.
 ©2024 Koroseal Interior Products, LLC.