



9 Colorways:	3B22-01 Pebble 3B22-02 Smoke 3B22-05 Pearl	3B22-06 Ebony 3B22-07 Truffle 3B22-15 Graphite	3B22-16 Alabaster 3B22-17 Java 3B22-18 Walnut
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	33 in.
Roll Width	54-55 in. (137-139 cm.)	Horizontal Repeat	54 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width	54 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating - Flame Spread - 10 - Smoke Developed - 5 NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover		
CE Certification	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
 ©2023 Koroseal Interior Products, LLC.

59-47-3B22-07/2022