

	<b>US UNITS</b>	<b>METRIC UNITS</b>
<b>Total Weight</b>	20 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	52" – 54"	132 - 137cm
<b>Gauge</b>	.027"	0.686 mm
<b>Fabric</b>	Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>CE Certification</b>	EU classification in accordance with EN 13501 – 1:2007 + EN15102:2007 + A1:2011 California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical 38.625" Horizontal 26" Nominal Pattern Width 52" Match Information Straight Match, Non-Reverse Hang	
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

**Available in 12 Colorways**

- 67170\*            67169\*
- 67160            67166\*
- 67165            67168\*
- 67161            67167\*
- 67164\*           67171
- 67163\*           67162

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.