

Koroseal® DEALS

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

DEALS P522

FACT SHEET

	US UNITS	METRIC UNITS
Total Weight	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	53/55 in.	134/140 cm
Gauge (avg)	0.020 in.	0.51 mm
Fabric	Nonwoven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec	CCC-W-408D, Type II	
WA Spec	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN-15102-2008	
Indoor Air Quality	California 01350 - Meets emission requirements for schools and offices	
Repeat	Vertical 18 in. Horizontal 52 in. Nominal Pattern Width 52 in. Match Information Straight Match, Non-Reverse Hang	45.72 cm 132 cm 132 cm
1 When applied to GRC Board with A-848-B adhesive	2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive	

Available in 1 Colorway

P522-18