

Carved Wood provides two unique looks in one design. Half of the line is treated using print to create a realistic multicolored wood grain effect. The other half of the line enhances the textural, grooved wood grain of the emboss with the use of an ink wipe over a solid ground. Both versions are sure to wow!

	US UNITS	METRIC UNITS
Total Weight	21.0 oz PLY 14.0 oz PSY	651 g PLM 475 g PSM
Roll Width	52/54 in.	132/137cm
Gauge	24 Mils	0.61 mm
Fabric	Non-Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	N/A
	Horizontal	1.25 in. 3.2 cm
	Nominal Pattern Width	51 in. 130 cm
	Match Information	Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 19 Colorways

- | | | |
|-------------|-------------|-------------|
| 69040 Pearl | 69048 Pearl | 69056 Ocean |
| 69041 Stone | 69049 Sand | 69057 Zinc |
| 69042 Zinc | 69050 Zinc | 69058 Pearl |
| 69043 Sand | 69051 Zinc | |
| 69044 Sand | 69052 Dawn | |
| 69045 Dawn | 69053 Sand | |
| 69046 Dawn | 69054 Stone | |
| 69047 Stone | 69055 Stone | |

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.

Arte® is a registered trademark of Arte N.V.

NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association

©2012 Koroseal Interior Products, LLC.