Koroseal®

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

ELEMENTS
BUILDING STANDARDS
Orion
FACT SHEET

		US UNITS	METRIC UNITS
Total Weight		20.0 oz PLY 13.3 oz PSY	651 g PLM 474.4 g PSM
Roll Width		52/54 in.	132/137 cm
Gauge		20 Mils	0.51 mm
Fabric		Woven	
Tensile (Minimum)		50 x 55 lb_f	222 x 245 N
Tear (Minimum)		25 x 25 lb_f	
Federal Spec		CCC-W-408A, Type II	
WA Spec		WA-101, Type II	
Fire Testing		NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test[1] Class A Rating NFPA 286 Corner Burn Test[2] Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	N/A	
	Horizontal	N/A	
	Nominal Pattern Width	51 in.	130 cm
	Match Information	Random Match, Reverse Hang	

1 When applied to GRC Board with A-848-B adhesive

2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 4 Colorways

*ELEM-40 Opal
*ELEM-41 Sand
*ELEM-42 Sea Glass
*ELEM-43 Frosted Jade

*Available in Traffic Patterns

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2017 Koroseal Interior Products, LLC.