

A horizontal fabric look, Amperage has the illusion of having some movement or interference similar to that of electrical static. Its multiple colored prints add depth and interest to this highly adaptable and functional product.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz PLY	452 gr/m2
Roll Width	52/54 in.	132/140 cm
Fabric	Osnaburg	
Federal Spec	CCC-W-408D, Type II	
WA Spec	WA-101, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 244 (ASTM E-84, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical	N/A
	Horizontal	N/A
	Nominal Pattern Width	51 in. 130 cm
	Match Information	Random Match, Reverse Hang
¹ When applied to GRC Board with A-848-B adhesive		² When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 15 Colorways

- | | |
|-------------------|----------------------|
| AMPR-01 Maxwell | AMPR-12 Electric Eel |
| AMPR-02 Voltage | AMPR-13 Frequency |
| AMPR-03 Watts | AMPR-14 Temperature |
| AMPR-04 Atoms | AMPR-15 Radon |
| AMPR-05 Polarized | |
| AMPR-06 Conductor | |
| AMPR-07 Current | |
| AMPR-08 Magnetism | |
| AMPR-09 Newton | |
| AMPR-10 Isotope | |
| AMPR-11 Charge | |