





D222-10 Earnest D222-71 Marie\*

D222-35 Naples D222-75 Portrait of a Lady\*

**9 Colorways:** D222-37 Expectation D222-91 Poplar

D222-55 Baroness D222-98 Smoke D222-70 Red Hilda

\*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent, and water.

Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	20.0 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	24 in.
Roll Width	53-55 in. (134-140 cm.)	Horizontal Repeat	13 in.
Backing	Non-Woven	Nominal Pattern Width	52 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test $^{1}$ 

- Class A Rating

Fire Testing

NFPA 286 Corner Burn Test<sup>2</sup>

- Meets requirements for Flame Spread, Smoke Developed, and Flashover

 $1\ When applied to\ GRC\ board\ with\ A-848-B\ adhesive\\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 2\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 3\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ applied\ to\ 5/8"\ Type-X-Gypsum\ board\ with\ A-848-B\ adhesive\\ 4\ When\ board\ with\ A-848-B\ adhesi$ 

**CE Certification** EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com