



15 Colorways:	8722-01 Brim	8722-06 Domra	8722-12 Hurdifell
	8722-02 Billow	8722-07 Apricity	8722-13 Holden
	8722-03 Burr	8722-08 Cymer	8722-14 Snicket
	8722-04 Hoodoo	8722-09 Achram	8722-50 Charcoal
	8722-05 Airie	8722-11 Pell	8722-89 Moss

Designer	Koroseal		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Non-woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II

NFPA 101® Life Safety Code®

Fire Testing	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011
------------------	--

Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices
--------------------	--

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.