

	US UNITS	METRIC UNITS
Total Weight	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
Roll Width	53/55 in.	135/140 cm
Gauge (avg)	0.024 in.	0.61 mm
Fabric	Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	
Federal Spec	CCC-W-408D, Type II	
WA Spec	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN-15102-2008	
Indoor Air Quality	California 01350- Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	9 in. 13.25 in. (with half drop at 6.625") 52in. Random Match, Reverse Hang
	¹ When applied to GRC Board with A-848-B adhesive	² When applied to 5/8" Type-X gypsum board with A-848-B adhesive

Available in 4 Colorways

- *ELEM-11 Sand Dollar
- *ELEM-12 Sea Horse
- *ELEM-13 Sea Otter
- *ELEM-14 Carribean

*Available in Traffic Patterns