

	US UNITS	METRIC UNITS
Total Weight	20 oz PLY	618 g PLM
	13.3 oz PSY	451 g PSM
Roll Width	52" – 54"	132 - 137cm
Fabric	Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
WA Spec	WA-101 - 2011, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® ASTM E-84 Tunnel Test - Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN15102:2007 + A1:2011 Fire Behavior – B Smoke Production – s2 Flame Droplets – d0	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical	N/A
	Horizontal	N/A
	Nominal Pattern Width	51"
	Match Information	Random Match, Non-Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 14 Colorways

67350	67355	67360
67351	67356	67361
67352	67357	67362
67353	67358	67363
67354	67359	