



8 Colorways:  
 UPL1-01  
 UPL1-06  
 UPL1-12  
 UPL1-13  
 UPL1-14  
 UPL1-15  
 UPL1-16  
 UPL1-19

<b>Designer</b>	Koroseal		
<b>Total Weight</b>	35.0 oz. ply (1082 g. plm.) 22.4 oz. psy (635 g. psm.)	<b>Vertical Repeat</b>	N/A
<b>Roll Width</b>	52 in. (132 cm.)	<b>Horizontal Repeat</b>	N/A
<b>Backing</b>	Woven (Osnaburg)	<b>Nominal Pattern Width</b>	52 in.
<b>Tensile (Minimum)</b>	N/A	<b>Match Information</b>	Reverse Hang, Straight Match
<b>Tear (Minimum)</b>	N/A	<b>WA Spec.</b>	WA-101, Type III
<b>Federal Spec.</b>	CCC-W-408D, Type III	<b>ASTM F-793</b>	Category VI, Type III
<b>Fire Testing</b>	NFPA 101® Life Safety Code®  NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating  NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, & Flashover  <small>1 When applied to GRC board with A-848-B adhesive</small>		
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011		
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices		
<b>For additional technical information please visit <a href="http://koroseal.com">koroseal.com</a></b>			

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | [koroseal.com](http://koroseal.com)

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.  
 Flex™ is a trademark of Koroseal Interior Products, LLC.  
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.  
 ©2024 Koroseal Interior Products, LLC.