

Geloom's large-scale, geometric pattern of intersecting fine lines form a connection with its companion Interloom. The use of metallics and pearls gives the line a multilayered identity.

	US UNITS	METRIC UNITS
Total Weight	20.0 oz. PLY 13.3 oz. PSY	620 g PLM 451 g PSM
Roll Width	52" – 54"	132 cm - 137 cm
Backing	Non-Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec.	CCC-W-408D, Type II	
WA Spec.	WA-101, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical 24" Horizontal 52" Nominal Pattern Width 51" Match Information Non-Reverse Hang, Straight Match	
1	When applied to GRC board with A-848-B adhesive	2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

Available in 10 Colorways

- | | |
|--------------------------|--------------------------------|
| *Frosted Coconut GM21-01 | *Cobalt Iridium GM21-06 |
| *Charred Coconut GM21-02 | Sheer Chiffon GM21-07 |
| *Hazelwood Fawn GM21-03 | Garden Chiffon GM21-08 |
| *Latte Mocha GM21-04 | *Infinite Silver Skies GM21-09 |
| *Steel Anchor GM21-05 | *Illuminated Abyss GM21-10 |

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.