



6 Colorways:
SL24-03
SL24-05
SL24-20
SL24-43
SL24-95
SL24-98

Designer	Koroseal		
Total Weight	24.0 oz. ply (744 g. plm.) 16.0 oz. psy (542 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	N/A
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408A, Type II	ASTM F-793	Category V, Type II

Fire Testing

NFPA 101® Life Safety Code®

NFPA 255 (ASTM E-84, CAN UL S102M) Tunnel Test¹
- Class A Rating

NFPA 286 Corner Burn Test²
- Meets requirements for Flame Spread, Smoke Developed, and Flashover

¹ When applied to GRC board with A-848-B adhesive ² When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive

CE Certification EU classification in accordance with EN 15102:2007 + A1:2011

Indoor Air Quality California 01350 – Meets emission requirements for schools and offices

For additional technical information please visit koroseal.com

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2024 Koroseal Interior Products, LLC.