Studios Maya VinylsTM

3875 Embassy Parkway Fairlawn, OH 44333

(800) 828-4556 www.koroseal.com



A subtle pattern and coloration that move with the light. Grassweave feels and looks like a natural grasscloth but is strong enough for the highest traffic areas.

		US UNITS	METRIC UNITS	
Total Weight		21.0 oz PLY 14.0 oz PSY	651 g PLM 474 g PSM	
Roll Width		54 in.	137 cm	
Gauge		23 Mils	0.58 mm	
Fabric		Osnaburg		
Tensile (Minimum)		50 x 55 lb _f	222 x 245 N	
Tear (Minimum)		25 x 25 lb _f		
Federal Spec		CCC-W-408A, Type II		
WA Spec		WA-101, Type II		
Fire Testing		NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover		
Repeat	Vertical	N/A		
	Horizontal Match Information	N/A Random Match, Revers	e Hang	
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

Available in 14 Colorways

GW21-54	Cabernet	GW21-40	Gunmetal*
GW21-34	Champagne	GW21-17	Linen
GW21-66	Copper*	GW21-05	Natural Linen
GW21-49	Desert Paint	GW21-38	Natural Silk
GW21-29	Golden Cloth*	GW21-98	Silver*
GW21-57	Golden Copper	GW21-12	Spring Wheat
GW21-84	Green Bamboo	GW21-43	Vanilla Bean

^{*} These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the wallcovering along with excessive scrubbing.