

Luminous rings rise and fall across a textured ground, evoking a playful sense of movement.

	US UNITS	METRIC UNITS
Nominal Weight	16.0 oz PLY 10.7 oz PSY	500 g PLM 360 g PSM
Weight Savings	Absence of chlorine provides a lower molecular weight polymer, therefore, making the wallcovering lighter for the same thickness. -Reduced freight costs -Easier handling of rolls for safety	
Roll Width	54/55 in.	134/140 cm
Fabric	Non-Woven	
Washability/Scrubability	Meets 300 Cycle Requirements	
Stain Resistance	Premium stain and abrasion resistant water-based coating applied	
Post Consumer Recycled Content	Contains a minimum of 20%	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Combustion Toxicity	Pittsburgh Protocol - Meets the New York City Requirements	
Indoor Air Quality	California 01350 - Tested to and meets emission requirements for schools and offices.	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 52 in. 132 cm Overlap and cut seams in stipple area- not through circles, Non-Reverse Hang
Does not contain chlorine or other halogen compound. Contains no plasticizers including phthalates. Printing inks are water-based.		
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 15 Colorways

K419-76 Aquamarine*	K419-90 Mineral*	K419-01 Simplicity
K419-46 Burnish*	K419-12 Nutria*	K419-23 Sungold*
K419-87 Celery*	K419-69 Penny*	K419-66 Taupestone*
K419-25 Coral*	K419-16 Porcelain	K419-39 Treasure*
K419-19 Eucalyptus*	K419-05 Silver*	K419-48 Umbrian Brown*

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the wallcovering along with excessive scrubbing.