

HIGH PERFORMANCE ECO-FABRIC FOR VERTICAL SURFACES Wallcoverings • Panel Systems • Partitions

tilizing a combination of pre-consumer and post-consumer recycled polyester to create unique performance yarns, Hytex Industries introduces our newest collection of vertical surface textiles for the commercial market.

SHIMMER SPECIFICATIONS

CONTENT

BACKING

FINISH

WEIGHT

WIDTH

ROLL SIZE

· 67% polyester · 33% olefin

acrylic

Crypton[®] 'Green' Soil & Stain Repellant

15 oz.

54"

50 yards

43 % RECYCLED CONTENT

· 10% post-consumer (polyester)

· 33% pre-consumer (olefin)

FLAMMABILITY
Passes: NFPA 286
Class A / ASTM E-84

FS: 20 SD: 50

Passes: Cal 117 Passes: Vertical Burn **ABRASION RESISTANCE**

(ASTM D-4157-02) 100,000 double rubs **COLOR FASTNESS TO LIGHT**

(AATCC-16A) Class 5.0 / 100 hrs.

ENVIRONMENTAL

does not contain:

- · pvc
- · chlorene
- · plasticizers
- · heavy metals
- · formaldehyde
- · ozone depleting substances
- · volatile organic chemicals (voc's)

conserving natural resources:

- · diverts waste from landfills
- · offsets the need to refine new crude oil
- · requires less energy to produce

R E P E V E° recycled yarns by unifi