

Koroseal® DEALS

3875 Embassy Parkway
Fairlawn, OH 44333

855.753.5474 koroseal.com

DEALS T228

FACT SHEET

	US UNITS	METRIC UNITS
Total Weight	28.0 oz. PLY 18.7 oz. PSY	867 g PLM 633 g PSM
Roll Width	52/54 in.	132/137 cm.
Gauge	36 Mils	0.91 mm.
Fabric	Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101, Type II	
Fire Testing	NFPA 101 [®] Life Safety Code [®] NFPA255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 51 in. 130 cm. Random Match, Reverse Hang

1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

Available in 4 Colorways

T228-07
T228-54
T228-81
T228-53