

	<b>US UNITS</b>	<b>METRIC UNITS</b>
<b>Total Weight</b>	20.0 oz PLY 13.3 oz PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	53/55 in.	134/140 cm
<b>Gauge (avg)</b>	0.22 in.	0.56 mm
<b>Fabric</b>	Non-Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec</b>	CCC-W-408D, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover EU classification in accordance with EN 13501-1:2007 and EN-15102-2008	
<b>Indoor Air Quality</b>	California 01350 - Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical Horizontal Nominal Pattern Width Match Information	N/A N/A 52 in. 132 cm Random Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" Type-X gypsum board with A-848-B adhesive

**Available in 5 Colorways**

- \*ELEM-06 Eternity
- \*ELEM-07 Moonlight
- \*ELEM-08 Eclipse
- \*ELEM-09 Daybreak
- \*ELEM-10 Indigo

\*Available in Traffic Patterns