

October 18, 2018

Koroseal Interior Products certifies TacWall tackable wallcovering:

- Contains 42% pre-consumer recycled content by weight per lineal foot
- 87% of TacWall composition is rapidly renewable (will regenerate in ten years or less)
- Has been tested to California Indoor Air Quality Specification 01350 and passed the testing. Testing was conducted by Berkeley Laboratories in Berkeley, California.

TacWall tackable wallcovering can contribute to buildings achieving the following points in the United States Green Building Council's LEED® rating systems:

- MR 3 LEED-Healthcare – Sustainably Sourced Materials
- MR 4.1 and 4.2 LEED-NC, LEED-CI, LEED-Schools, Retail – Recycled Content
- MR 6 LEED-NC, LEED-CI, LEED-Schools, LEED-Retail – Rapidly Renewable Materials
- EQ 4 LEED-Schools, Retail, Healthcare – Low-Emitting Materials

Koroseal Interior Products also certifies that L910 adhesive used to install TacWall tackable wallcovering:

- Is water based and contains 0 VOCs (meets South Coast Air Quality Management District Rule #1168)

L910 adhesive used to install TacWall wallcovering can contribute to a building achieving the following points in the United States Green Building Council's LEED® rating systems:

- EQ 4.1 LEED-NC, LEED-CI, LEED-Schools, LEED-Retail, LEED-Healthcare – Low-Emitting Adhesives & Sealants

Please contact me at 330-668-7638 with any questions.

Regards,



Thomas C. Roche LEED AP ID+C
Koroseal Interior Products