



12 Colorways:	67980 White Smoke	67986 Slate
	67981 Pearl	67987 Chestnut
	67982 Warm Grey	67988 Pebble Grey
	67983 Sand	67989 Clay
	67984 Stone	67990 Ochre
	67985 Tartufo	67991 Pecan

Designer	Arte®		
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices LINK		
Environmental Product Declaration (EPD)	LINK		
Health Product Declaration (HPD)	LINK		

For additional technical information please visit koroseal.com

1111 Medina Road | Medina, OH 44256 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
Arte® is a registered trademark of Arte N.V.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2026 Koroseal Interior Products, LLC.