

**Indoor Air Quality** 







8 Colorways:	SG02-01 Sandstone SG02-02 Mica SG02-03 Zinc SG02-04 Terra Verte	SG02-05 Clay SG02-06 Graphite SG02-07 Prussian Blue SG02-08 Alabaster	
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat	24 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	52 in.
Backing	Non-Woven	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb <sub>f</sub> (222 x 245 N)	Match Information	Non-Reverse Hang, Straight Match
Tear (Minimum)	25 x 25 lb <sub>f</sub> (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®  NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test <sup>1</sup> - Class A Rating - Flame Spread - 10 - Smoke Developed - 5  NFPA 286 Corner Burn Test <sup>2</sup> - Meets requirements for Flame Spread, Smoke Developed, & Flashover  1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

California 01350 - Meets emission requirements for schools and offices