

# **FLEX™ DECORATIVE WALL PROTECTION CLEANING INSTRUCTIONS**



Flex Decorative Wall Protection is protected with a durable, acrylic top coat which provides superior stain resistance.

Stains should be removed as quickly as possible to eliminate any possible reaction between the staining agent and the wallcovering. Time is especially important for removing materials containing colors or solvents such as ball point ink, nail polish, lipstick, oil shampoo tints, paint, lacquer or enamel and some foodstuffs.

## **PRECAUTIONS**

Excess soiling materials such as chewing gum, asphalt, crayons, paint, nail polish, or tar should be carefully scraped off prior to other cleaning attempts.

## **CLEANING**

The normal cleaning of the wallcoverings should be done with mild ingredients such as soap, detergent, and water. If stained and stronger cleaning is required the use of liquid household cleaner should be used.

Metallic Finishes can be discolored with the use of caustic cleaners and we recommend only the use of mild soap solution for cleaning of these products. If stronger cleaning is required, first evaluate the cleaner in an inconspicuous location.

The method of cleaning should be to use a sponge and the mild soap solution. A natural sponge's construction does the best job of removing dirt from the textured surface.

With difficult to remove deposits, the use of soft bristle brush is recommended. Then rinse thoroughly with clean, clear water, changing water often to insure it remains clean and clear. After cleaning an area, be sure to dry with an absorbent cloth so it can be examined to assure complete cleaning.

**NEVER MIX CLEANING REAGENTS TOGETHER – VIOLENT REACTIONS MAY OCCUR WHICH COULD RESULT IN SERIOUS INJURY. OBSERVE ALL LABEL AND PRECAUTIONS WHEN USING THESE AND ANY CLEANING REAGENTS.**

Repeated use of stronger cleaners will extract plasticizer from vinyl wallcoverings causing the wallcovering to lose its suppleness.

Cleaning products that contain solvents or alcohol should not be used.

Flex Decorative Wall Protection products that do NOT contain metallics are bleach cleanable. The bleach should be diluted at a ratio of 4:1.