


15 Colorways:

AN24-01 Gypsum
AN24-02 Kaolin
AN24-03 Tara
AN24-04 Oak Nut
AN24-05 Titanium

AN24-06 Limestone
AN24-07 Woad*
AN24-08 Comflower
AN24-09 Walnut Hulls
AN24-10 Ancient Earth

AN24-11 Vivianite
AN24-12 Lampblack*
AN24-13 Slate
AN24-14 Madder Root*
AN24-15 Indigo*

*These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water.
Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.

Designer	Koroseal		
Total Weight	24 oz. ply (743 g. plm.) 16 oz. psy (542 g. psm.)	Vertical Repeat	N/A
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat	N/A
Backing	Woven (Osnaburg)	Nominal Pattern Width	51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information	Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec.	WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793	Category V, Type II
Fire Testing	NFPA 101® Life Safety Code®		
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating		
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover		
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive		
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011		
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices LINK		
Environmental Product Declaration	LINK		
Health Product Declaration (HPD)	LINK		

For additional technical information please visit koroseal.com

1111 Medina Road | Medina, OH 44256 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
©2025 Koroseal Interior Products, LLC.