

	US UNITS	METRIC UNITS
<b>Total Weight</b>	20.0 oz. PLY 13.3 oz. PSY	618 g PLM 451 g PSM
<b>Roll Width</b>	53" – 55"	135 cm - 140 cm
<b>Backing</b>	Non-Woven	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	111 x 111 N
<b>Federal Spec. WA Spec.</b>	CCC-W-408D, Type II WA-101, Type II	
<b>ASTM F-793</b>	Category V, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test <sup>1</sup> Class A Rating Flame Spread - 10 Smoke Developed - 5 NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed & Flashover	
<b>CE Certification</b>	EU classification in accordance with EN 15102:2007 + A1:2011	
<b>Indoor Air Quality</b>	California 01350 – Meets emission requirements for schools and offices	
<b>Repeat</b>	Vertical 24" Horizontal 52" Nominal Pattern Width 51" Match Information Non-Reverse Hang, Straight Match	
<sup>1</sup> When applied to GRC board with A-848-B adhesive	<sup>2</sup> When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive	

## Available in 5 Colorways

- \*67520
- 67521
- \*67522
- \*67523
- \*67524

\* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.