

	US UNITS	METRIC UNITS
Total Weight	21 oz PLY 14 oz PSY	651 g PLM 475 g PSM
Roll Width	52" – 54"	132 - 137cm
Gauge	.024"	0.61 mm
Fabric	Woven	
Tensile (Minimum)	50 x 55 lb _f	222 x 245 N
Tear (Minimum)	25 x 25 lb _f	111 x 111 N
Federal Spec	CCC-W-408A, Type II	
WA Spec	WA-101 - 2011, Type II	
ASTM F-793	Category V, Type II	
Fire Testing	NFPA 101® Life Safety Code® NFPA 255 (UL723, CAN S102M) Tunnel Test ¹ Class A Rating NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN15102:2007 + A1:2011 Fire Behavior - B Smoke Production - s2 Flame Droplets - d0 California 01350 – Meets emission requirements for schools and offices	
Indoor Air Quality		
Repeat	Vertical	N/A
	Horizontal	N/A
	Nominal Pattern Width	51"
	Match Information	Random Match, Non-Reverse Hang
1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

Available in 14 Colorways

67330	67335	67340
67331	67336	67341
67332	67337	51120
67333	67338	51131
67334	67339	