

# Koroseal® DEALS

3875 Embassy Parkway  
Fairlawn, OH 44333

855.753.5474 koroseal.com

# DEALS PV26

## FACT SHEET

	US UNITS	METRIC UNITS
<b>Total Weight</b>	26.0 oz PLY 17.3 oz PSY	806 g PLM 587.6 g PSM
<b>Roll Width</b>	54 in.	137 cm
<b>Gauge</b>	27 Mils	0.68 mm
<b>Fabric</b>	Osnaburg	
<b>Tensile (Minimum)</b>	50 x 55 lb <sub>f</sub>	222 x 245 N
<b>Tear (Minimum)</b>	25 x 25 lb <sub>f</sub>	
<b>Federal Spec</b>	CCC-W-408A, Type II	
<b>WA Spec</b>	WA-101, Type II	
<b>Fire Testing</b>	NFPA 101® Life Safety Code® NFPA255 (UL723, CAN S102M) Tunnel Test <sup>1</sup> Class A Rating NFPA 286 Corner Burn Test <sup>2</sup> Meets requirements for Flame Spread, Smoke Developed and Flashover	
<b>Repeat</b>	Vertical Horizontal Match Information	N/A N/A Straight Match, Reverse Hang
1 When applied to GRC Board with A-848-B adhesive		2 When applied to 5/8" type-X gypsum board with A-848-B adhesive

## Available in 5 Colorways

PV26-05  
PV26-39  
PV26-43  
PV26-51  
\*PV26-56

**\*This decorative metallic wallcovering should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.**