

	US UNITS	METRIC UNITS
Total Weight	15 oz PLY 10 oz PSY	464 g PLM 339 g PSM
Roll Width	52" – 54"	132 - 137cm
Gauge	.018"	0.457 mm
Fabric	Woven	
Tensile (Minimum)	30 x 30 lb _f	133 x 133 N
Tear (Minimum)	12 x 12 lb _f	
Federal Spec	CCC-W-408D, Type I	
WA Spec	WA-101, Type I	
ASTM F-793	Category IV, Type I	
Fire Testing	NFPA 101® Life Safety Code® NFPA255 (ASTM E-84, CAN S102M) Tunnel Test ¹ Class A Rating Flame Spread 10 Smoke Developed 5 NFPA 286 Corner Burn Test ² Meets requirements for Flame Spread, Smoke Developed and Flashover	
CE Certification	EU classification in accordance with EN 13501 – 1:2007 + EN15102:2008	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
Repeat	Vertical Horizontal Nominal Pattern Width Match Information	N.A N/A 51" Reverse Hang
1 When applied to GRC Board with A-848-B adhesive 2 When applied to 5/8" type-X gypsum board with A-848-B adhesive		

Available in 16 Colorways

67109 67100 67105
 67110* 67102 67104
 67101 67106 67112
 67111 67103 67107
 67114 67115
 67113 67108

* These decorative metallic wallcoverings should only be cleaned with mild ingredients such as soap, detergent and water. Stronger, more alkaline household cleaners have the potential to damage the surface of the material along with excessive scrubbing.