



7 Colorways:	SP81-01 Tuxedo SP81-02 Fog SP81-06 Blush SP81-07 Major Grey	SP81-11 Cobblestone SP81-12 Causeway SP81-19 Seafoam
Designer	Koroseal	Vertical Repeat 18 in.
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g. psm.)	Horizontal Repeat 26.5 in.
Roll Width	52-54 in. (132-137 cm.)	Nominal Pattern Width 51 in.
Backing	Non-Woven	Match Information Non-Reverse Hang, Straight Match
Content	Thermo Polymer Olefin	WA Spec. WA-101, Type II
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	ASTM F-793 Category V, Type II
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	Federal Spec CCC-W-408D, Type II
Fire Testing	NFPA 101® Life Safety Code®	
	NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test ¹ - Class A Rating	
	NFPA 286 Corner Burn Test ² - Meets requirements for Flame Spread, Smoke Developed, & Flashover	
	1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	
For additional technical information please visit koroseal.com		

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
 NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association.
 ©2024 Koroseal Interior Products, LLC.