

5:97"G o dcuu{"Retmyc{"
 Hcktn c y p."QJ""66555"
 :77097507696" "mqtqugcnleq o"

Nkmg"vjg"ncpfuecrg"qh"c"htqtuv."Pqt fke"ecrvwtgu"vjg"dcuke"dgcvv{"cpf"rgceghwn"vppgu"qh"o cp{"yqqf"urgekgu0

| | US UNITS | METRIC UNITS |
|--|--|--|
| Total Weight | 57"q 0"RN [4406"q 0"RU [74"kp0 | "i"RNO"***** 857"i"RUO 354"eo0 |
| Roll Width | 74"kp0 | 354"eo0 |
| Backing | Y qxgp" | |
| Federal Spec. | EEE/Y/62:F."V{rg"KKK | |
| WA Spec. | YC/323."V{rg"KKK | |
| ASTM F-793 | Ecvgiqt{"X."V{rg"KKK | |
| Fire Testing | NFPA 101® Life Safety Code® NFPA 255 (ASTM E-84, CAN S102M)) Tunnel Test ¹ | |
| Indoor Air Quality | Encuu"C"Tvcp i" Hnc o g"Urtgef"6"32" U o qmg" Fg xgnqrgf"6"7" | |
| Repeat | Xgtvkecn" J qtk qpvcn" Pq o kpcn"Kphqt o cvkqp" Ocvej"Kphqt o cvkqp" | P1C" P1C" 74"kp0 Pqp/Tgxgtug" J cpi."Tcpf q o "Ocvej |
| 3""Y jgp"cr rnk g f"vq" I TE"dqctf"ykvj"C/:6:/D"cf j gukxg"" | | 4""Y jgp"cr rnk g f"vq"7l:6"V{rg/Z/I {ruw o"dqctf"ykvj"C/:6:/D"cf j gukxg" |

Available in 8 Colorways

- PTF3/34" Y cu j g f
- PTF3/;3" Y gcvjgtg f
- PTF3/68"Dgc o
- PTF3/;7"U o qmg f
- PTF3/36"O crng
- PTF3/64"Cuj
- PTF3/66"Vgcm
- PTF3/6:" Y cnpwv

Mqtqugcn¹"lu" c"tg i kvgtg f"vte fg o ctm"qh" Mqtqugcn"Xpigtkt"Rtq fweu."NNE0"
 Hgz²0"lu" c"vte fg o ctm"qh" Mqtqugcn"Xpigtkt"Rtq fweu."NNE0"
 PHRC"3231"cpf"Nhig"Uchgv{"Eqfg"1"ctg"tg i kvgtg f"vte fg o ctm"qh" Pevkpcn" Hltg"Rtgxgpvkq" Cuuqelcvkq0
 I 4242" Mqtqugcn"Xpigtkt"Rtq fweu."NNE0"