



9 Colorways:	SG06-01 Alabaster SG06-02 Aluminum SG06-03 Cement SG06-04 Steel SG06-05 Silt	SG06-06 Sandstone SG06-07 Jade SG06-08 Blue Kyanite SG06-09 Quartzite
Total Weight	20 oz. ply (618 g. plm.) 13.3 oz. psy (451 g psm.)	Vertical Repeat 18 in.
Roll Width	52-54 in. (132-137 cm.)	Horizontal Repeat 52 in.
Backing	Woven (Osnaburg)	Nominal Pattern Width 51 in.
Tensile (Minimum)	50 x 55 lb _f (222 x 245 N)	Match Information Reverse Hang, Random Match
Tear (Minimum)	25 x 25 lb _f (111 x 111 N)	WA Spec. WA-101, Type II
Federal Spec.	CCC-W-408D, Type II	ASTM F-793 Category V, Type II
Fire Testing	<p>NFPA 101® Life Safety Code®</p> <p>NFPA 255 (ASTM E-84, CAN S102M) Tunnel Test¹</p> <ul style="list-style-type: none"> - Class A Rating - Flame Spread - 10 - Smoke Developed - 5 <p>NFPA 286 Corner Burn Test²</p> <ul style="list-style-type: none"> - Meets requirements for Flame Spread, Smoke Developed, & Flashover <p><small>1 When applied to GRC board with A-848-B adhesive 2 When applied to 5/8" Type-X-Gypsum board with A-848-B adhesive</small></p>	
CE Certification	EU classification in accordance with EN 15102:2007 + A1:2011	
Indoor Air Quality	California 01350 – Meets emission requirements for schools and offices	

3875 Embassy Parkway | Fairlawn, OH 44333 | 855.753.5474 | koroseal.com

Koroseal® is a registered trademark of Koroseal Interior Products, LLC.
Stacy Garcia New York® and Stacy Garcia® are registered trademarks of Stacy Garcia, Inc.
NFPA 101® and Life Safety Code® are registered trademarks of National Fire Prevention Association
©2022 Koroseal Interior Products, LLC.